



RIGLINK DMX Cables

This durable, double-shielded Riglink DMX cable is a production-grade solution engineered for exceptionally stable signal transmission. Perfect for professional touring, live productions, and permanent installations where signal integrity and robust construction are essential.

- Protects signal integrity with a double shield of braided and aluminum foil layers.
- Delivers stable 110-ohm impedance using high-torsion tinned oxygen-free copper conductors.
- Equipped with professional-grade Seetronic® connectors for reliable and secure connections.
- Housed in a highly elastic PVC jacket for exceptional durability and flexible handling.
- Simplifies setup with color-coded connectors for fast identification of different cable lengths.
- Ensures stable signal transmission with low-dielectric LDPE insulation for precise impedance.

SPECIFICATIONS

Construction / Physical	Connections
Conductor Specification: 2 x 0.22mm ² (24AWG)	Connector: Seetronic SCM55-BG
Conductor Structure: OFC 20/0.12BC	Connector: Seetronic SCMF5-BG
Insulation Material: LDPE	
Insulation OD: 1.8mm	
Shield Structure: OFC 16/8/0.1TC + AL	
Outer Jacket Material: PVC (Black)	
Outer Diameter: 6.0 ± 0.2mm	
Temperature Rating: -20°C – 70°C	
IP Rating: IP20	
	Electrical
	Withstand Voltage: 0.5kV
	Conductor Resistance: 88.2 Ω/km
	Capacitance between Conductors: 50 pF/m
	Conductor and Sheild Capacitance: 122 pF/m
	Impedance: 110 Ω
	Cable
	Metric: 1m, 3m, 5m, 10m, 20m
	Imperial: 1.5ft, 5ft, 10ft, 25ft, 50ft

VARIATIONS

Length	SKU	Description
1.5FT	RIGLINKDMX18IN	RIGLINK DMX Cables – 1.5FT
1M	RIGLINKDMX1M	RIGLINK DMX Cables – 1M
5FT	RIGLINKDMX5FT	RIGLINK DMX Cables – 5FT
3M	RIGLINKDMX3M	RIGLINK DMX Cables – 3M
10FT	RIGLINKDMX10FT	RIGLINK DMX Cables – 10FT
5M	RIGLINKDMX5M	RIGLINK DMX Cables – 5M
25FT	RIGLINKDMX25FT	RIGLINK DMX Cables – 25FT
10M	RIGLINKDMX10M	RIGLINK DMX Cables – 10M
50FT	RIGLINKDMX50FT	RIGLINK DMX Cables – 50FT

Length	SKU	Description
20M	RIGLINKDMX20M	RIGLINK DMX Cables – 20M