



RIGLINK PowerKon Cables

A UL-certified, professional-grade power cable designed with flexible copper-stranded wire and durable Seetronic® connectors for safe and reliable power delivery.

Perfect for powering professional audio, video, and lighting equipment in demanding live event, touring, and stage production environments.

- Built with stranded oxygen-free copper conductors for clean, consistent power delivery.
- Offers a rugged, versatile design suitable for demanding touring and installation use.
- Equipped with professional-grade Seetronic® connectors ensuring a robust and secure link.
- Features UL-certified components that meet global safety standards for international use.
- Simplifies setup with color-coded connectors for quick identification of cable lengths.
- Available in multiple standard lengths to suit a wide range of production needs.

SPECIFICATIONS

Construction / Physical

Conductor Specification: 3 x 2.08mm² (14AWG)

Conductor Structure: OFC 41/0.25BC

Insulation Material: PVC

Insulation OD: 3.45mm

Outer Jacket Material: PVC (Black)

Outer Diameter: 9.2 ± 0.2mm

Temperature Rating: -20°C – 105°C

IP Rating: IP20

Connections

Connectors:

Connector: Seetronic SAC3FCA

Connector: Seetronic SAC3FCB

Electrical

Voltage Rating: 300 V/500 V

Conductor Resistance: 7.8 Ω/km

Cable

Imperial: 1.5ft, 5ft, 10ft, 25ft

VARIATIONS

Length	SKU	Description
1.5FT	RIGLINKPOWERKON18IN	RIGLINK PowerKon Cables – 1.5FT
1M	RIGLINKPOWERKON1M	RIGLINK PowerKon Cables – 1M
5FT	RIGLINKPOWERKON5FT	RIGLINK PowerKon Cables – 5FT
3M	RIGLINKPOWERKON3M	RIGLINK PowerKon Cables – 3M
10FT	RIGLINKPOWERKON10FT	RIGLINK PowerKon Cables – 10FT
5M	RIGLINKPOWERKON5M	RIGLINK PowerKon Cables – 5M
25FT	RIGLINKPOWERKON25FT	RIGLINK PowerKon Cables – 25FT
10M	RIGLINKPOWERKON10M	RIGLINK PowerKon Cables – 10M