



Rogue Outcast 1 BeamWash

A lightweight, IP65-rated LED fixture combining beam and wash effects with a wide zoom range and a pixel-mappable outer ring for creative visual impact.

Ideal for touring productions, festivals, and any event requiring a compact, all-weather fixture that delivers a versatile range of beam, wash, and pixel effects.

- Features seven 45W RGBW LEDs, producing a punchy and vibrant 4,073-lumen output.
- Delivers a wide 3.9° to 55.3° zoom range for flexible beam or wash applications.
- Create dynamic visuals with a 12-zone, pixel-mappable RGB ring under a stealth filter.
- Provides advanced control with 16-bit dimming, six dimming modes, and selectable PWM settings.
- A compact, 20 lb IP65-rated body ensures all-weather reliability for touring and events.
- Offers versatile control via DMX and RDM, plus a USB-C port for easy software updates.

SPECIFICATIONS

Optical

Field Angle: 5.9° to 49.8°

Cutoff Angle: 6.7° to 55.3°

Zoom Range: 3.9° to 55.3°

Lumens – Source: 5,900

Lumens – Output: 4,073

Illuminance:

Illuminance (3.9°): 15,308 lux @ 5 m

Illuminance (55.3°): 473 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/260°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 260° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: yes

Recall Custom Programs: No

Construction / Physical

Dimensions: 11.92 x 7.58 x 15.75 in (303 x 192 x 391 mm)

Weight: 20.2 lb (9.16 kg)

Exterior Color: Black

Housing Material: Magnesium aluminum diecast, high impact, flame-retardant polymer

Connections

Power Connection: Edison plug to Seetronic Powerkon IP65

Power Input: Seetronic Powerkon IP65

Power Output: Seetronic Powerkon IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 15, 24, 30, 64, 111 or 135

Modes/Personalities: 6 personalities (15, 24, 30, 64, 111, 135)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 3 units @ 120 V; 6 units @ 208 V; 7 units @ 230 V

Power and Current: 385 W, 3.25 A @ 120 V, 60 Hz

Power and Current: 376 W, 1.92 A @ 208 V, 60 Hz

Power and Current: 372 W, 1.69 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Maximum Exterior Surface Temperature (Tc): 80° C / 176° F

Maximum Ambient Temperature (ta): 45° C / 113° F

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

IP Rated Seetronic® Powerkon Extensions

DMX Cables

Flight Case:

UPLOAD 08 software uploader

What's Included

Rogue Outcast 1 BeamWash

Seetronic Powerkon IP65 power cord

(2) Omega brackets with mounting hardware