

PJ-202DL

Bidirectional Projection Speaker

The PJ-202DL-EB is certified according to the European Standard EN 54-24: 2008, and compliant with the British Standard BS 5839-8: 2008 14.8. The PJ-202DL-EB is a bidirectional projection speaker designed for wall or ceiling installation in indoor and outdoor applications.



Article number: PJ-202DL-EB

Specifications

Frequency response	120 Hz - 20 kHz (-10 dB from sensitivity)
Sensitivity (1#V, 1#m)	88 dB (100 Hz - 10 kHz, pink noise, both chassis driven)
Directivity Angle catalogue output	500 Hz x 2: 130°/130° 1 kHz x 2: 155°/155° 2 kHz x 2: 155°/155° 4 kHz x 2: 60°/60°
Rated input (High Impedance)	20 W
Tappings	100 V: 500 Ω (20 W) / 1 kΩ (10 W) / 2 kΩ (5 W)
Maximum sound pressure level (1 m)	101 dB (100 Hz - 10 kHz, pink noise, both chassis driven)
Connection	Ceramic screw terminals
Operating temperature	-25 °C to +70 °C
Speaker component	2 x 12 cm cone-type
Certificates	EN 54-24, BS, IP44, Ease
Dimensions	146 x 186 mm (Ø x D)
Gross weight	3,8 KG
Finish	Aluminium, white,
Weight	3.2 kg

PJ-202DL

Bidirectional Projection Speaker

Appearance

